







# MARINE GUARD™ Foam Filled Fenders

## 8.0 ft (2.4 m) Diameter x 20.0 ft (6.1 m) Long

### Standard Capacity



8.0 Ft. DIAMETER x 20.0 Ft. LONG	English	Metric
<b>PERFORMANCE* (AT 60% COMPRESSION)</b>		
Energy absorption, ft-kip (ton-m)	961	133
Reaction force, kip (ton)	447	203
<b>DIMENSIONS AND WEIGHT</b>		
Diameter, ft (m)	8.0	2.4
Length eye-to-eye, ft (m)	20.0	6.1
Length of flat, ft (m)	14.1	4.3
Skin thickness, in (mm)	1.63	41
Weight, lb. (kg)	7,600	3,450
Cube, ft <sup>3</sup> (m <sup>3</sup> )	1,360	39
<b>TECHNICAL DATA</b>		
Standoff distance:		
Maximum, ft (m)	8.0	2.4
At 60% compression, ft (m)	3.2	1.0
Safe working end-pull load, kip (kN)	70	311
<b>FOOTPRINT (AT 60% COMPRESSION)</b>		
Maximum width, ft (m)	10.0	3.0
Maximum length, ft (m)	16.3	5.0
Area, ft <sup>2</sup> (m <sup>2</sup> )	124.2	11.5
<b>RECOMMENDED SIZES OF MOUNTING HARDWARE</b>		
Chain, in (mm)	2.00	51
Shackles, in (mm)	2.00	51
Swivels, in (mm)	2.00	51



\*Above information is for our Standard Capacity *Marine Guard*™ foam filled marine fenders. Actual values for all sizes may vary plus or minus 15% from stated values due to variations in material properties, dimensional tolerances, temperature and speed of compression.